Mecánica Computacional Vol XXXV, págs. 1297-1297 (resumen) Martín I. Idiart, Ana E. Scarabino y Mario A. Storti (Eds.) La Plata, 7-10 Noviembre 2017

SPACE-CHARGE POLARIZATION IN MICROSTRUCTURED SOLID DIELECTRICS

Cristian J. Bottero and Martín I. Idiart

Departamento de Aeronáutica, Facultad de Ingeniería, Universidad Nacional de La Plata, Avda. 1 esq. 47 S/N, La Plata B1900TAG, Argentina

Consejo Nacional de Investigaciones Científicas y Técnicas (CONICET), CCT-La Plata, Calle 8 Nº 1467, La Plata, B1904CMC, Argentina.

Keywords: heterogeneous materials; nonlinearity; variational methods; electrostatics; mobile ions

Abstract. The electromechanical response of deformable solid dielectrics strongly depends on their polarizability, which is often the result of several concomitant micromechanisms of diverse origin. When a specimen possesses a fine microstructure and contains a certain amount of mobile ions, the intrinsic polarization of atomic and molecular origin can be significantly enhanced by an extrinsic polarization produced by space charges around microstructural interfaces blocking the flow of ions. This spacecharge polarization is often found, for instance, in polycrystalline ceramics at low-frequency loadings, and has been recently proposed as a possible micromechanism responsible for the extreme dielectric enhancements observed in certain nanofilled polymers and perovskite-type ceramics. This work presents a continuum multiscale description for the electrostatic response of microstructured solid dielectrics undergoing intrinsic and space-charge polarization. To ease the presentation, attention is restricted to mechanically rigid solids containing a single species of mobile ions. The formulation can, however, be adapted to more complex systems. The relevant field equations of electrostatics are recast in the form of a minimum energy principle for the electrostatic and chemical potentials, and a two-scale version of the principle in terms of an effective energy density is then proposed. Elementary bounds and approximate estimates for the effective energy density are also provided. By way of example, the formulation is used to explore the dependence of the macroscopic response upon microstructural morphology in multiphase layered media, with focus on constitutive nonlinearity and microstructural size effects.